

HPCNFW WICK - BURN CHART

The HPCNFW chart was based on our standard tests results. The results represent cycle of four hours, made with 145 fully paraffin wax refined.

S.V	Product style SV	Mts/Kg	Flame Ht		Consumption Rate		Pool Diameter	
			In Inches	In Cm	Ounces/Hr	Grams/Hr	In Inches	In Cm
A8137	HP 991 CNFW	1996	0,83	2,10	0,09	2,60	1,18	3,00
A8135	HP 807 CNFW	1626	0,94	2,40	0,13	3,82	1,57	4,00
A8150	HP 665 CNFW	1339	0,94	2,40	0,14	3,95	1,77	4,50
A8125	HP 644 CNFW	1298	1,18	3,00	0,15	4,16	1,97	5,00
A8155	HP 621 CNFW	1250	1,22	3,10	0,15	4,18	1,97	5,00
A8160	HP 594 CNFW	1196	1,28	3,25	0,15	4,20	1,97	5,00
A8130	HP 487 CNFW	980	1,30	3,30	0,17	4,80	1,69	4,30
A8120	HP 483 CNFW	973	1,30	3,30	0,17	4,85	1,69	4,30
A8115	HP 460 CNFW	926	1,38	3,50	0,17	4,85	1,69	4,30
A8110	HP 414 CNFW	833	1,57	4,00	0,19	5,40	1,97	5,00
A8100	HP 379 CNFW	763	1,57	4,00	0,20	5,60	1,97	5,00
A8140	HP 290 CNFW	585	1,77	4,50	0,23	6,62	2,17	5,50
A8145	HP 180CNFW	363	1,97	5,00	0,30	8,45	2,64	6,70

- Additional sizes and developments available on request.

