

HPC WICK - BURN CHART

The HPC chart was based on our standard tests results. The results represent cycle of four hours, made with 145 fully paraffin wax refined.

S.V	Style	Mts/Kg	Flame Ht		Consumption Rate		Pool Diameter	
	S.V		In Inches	In Cm	Ounces/Hr	Grams/Hr	In Inches	In Cm
B7025	HP 986 C	1986	0,98	2,5	0,08	2,25	1,81	4,6
B2010	HP 945 C	1904	0,91	2,3	0,08	2,3	1,81	4,6
B7015	HP 776 C	1563	0,87	2,21	0,12	3,31	2,09	5,3
B7030	HP 612 C	1233	0,94	2,4	0,13	3,56	2,13	5,4
B2015	HP 655 C	1319	1,3	3,3	0,13	3,73	2,6	6,6
B2065	HP 600 C	1209	1,46	3,7	0,14	3,98	2,28	5,8
B2000	HP 628 C	1219	1,38	3,5	0,15	4,19	2,09	5,3
B7020	HP 557 C	1121	1,54	3,9	0,15	4,34	2,32	5,9
B2020	HP 484 C	974	1,57	4	0,17	4,74	2,4	6,1
B2025	HP 450 C	907	1,65	4,2	0,23	6,57	2,48	6,3
B2030	HP 300 C	605	2,17	5,5	0,25	7,01	2,6	6,6
B2035	HP 200 C	403	2,64	6,7	0,28	7,89	4,25	10,8

