

## HPC WICK - BURN CHART

The HPC chart was based on our standard tests results. The results represent cycle of four hours, made with 145 fully paraffin wax refined.

S.V	Style S.V	Mts/Kg	Flame Ht		Consumption Rate		Pool Diameter	
			In Inches	In Cm	Ounces/Hr	Grams/Hr	In Inches	In Cm
B7025	HP 986 C	1986	0,98	2,50	0,08	2,25	1,81	4,60
B2010	HP 945 C	1904	0,91	2,30	0,08	2,30	1,81	4,60
B7015	HP 776 C	1563	0,87	2,21	0,12	3,31	2,09	5,30
B7030	HP 612 C	1233	0,94	2,40	0,13	3,56	2,13	5,40
B2015	HP 655 C	1319	1,30	3,30	0,13	3,73	2,60	6,60
B2065	HP 600 C	1209	1,46	3,70	0,14	3,98	2,28	5,80
B2000	HP 628 C	1219	1,38	3,50	0,15	4,19	2,09	5,30
B7020	HP 557 C	1121	1,54	3,90	0,15	4,34	2,32	5,90
B2020	HP 484 C	974	1,57	4,00	0,17	4,74	2,40	6,10
B2025	HP 450 C	907	1,65	4,20	0,23	6,57	2,48	6,30
B2030	HP 300 C	605	2,17	5,50	0,25	7,01	2,60	6,60
B2035	HP 200 C	403	2,64	6,70	0,28	7,89	4,25	10,80

- Additional sizes and developments available on request

